




DRILL GRINDING MACHINE BSG 60

ITEM NO. 11323

The professional machine – **Basic version**

The professional machine for supreme claims. For drills from Ø 3 – 60 mm. Precise, no servicing, 4 point linear quideways.

Spindle system with adjustable needle bearings. Prism quick action system.



- ✓ clamping range from Ø 3 40 mm
- ✓ range extension to 60 mm by extra prism
- clearance- and top angle to be adjusted stepless



- patented prism reversing system
- ✓ web thinning
- optional: countersink-and cutter grinding adaptor SZVR (see page. 20)



Technical data

Ø 3 to 60 mm Clamping range: Corundum grinding wheel: 200 x 40 x 51 mm Motor: 230 V, 50 Hz, 0,37 kW

(also avaliable in 400 V, 110 V, 60 Hz)

Revolutions: 2800 rpm⁻¹ Weight net: 57 kg

Clearance- and top angle: to be adjusted stepless Dim (L x W x H): 570 x 330 x 520 mm

Basic version

- Prism from Ø 3 to 40 mm
- Corundum grinding wheel grit 60
- Precision optical lens lighted
- Grinding wheel dresser with rotating diamond

K100



Carbide drills



Cutters



Step drills



Flat drill



Extra prism clamping range Ø 40 - 60 mm

Item No. 10602

Item No. 10627

Item No. 17480

K180



Center tip for wood



Center tip for sheet metal





Cross facet ground



Left hand drill



edge correction



Diamond grinding wheel

Ø 200 mm incl. support

CBN-grinding wheel

Ø 200 mm incl. support



200x40x51 Item No. 10612 Item No. 10613 Item No. 10614 Item No. 10615

200x20x51 Item No. 10687 Item No. 10688 Item No. 10689 200x 8x51 Item No. 10691 Item No. 10692 Item No. 10693



Countersink sharpening device SVR 31

K46

incl. collet 10 mm Item No. 10583

K60



Collet set

for SVR 31 (Ø 6, 8, 12 mm) Item No. 14348



Nut for extra collets

Item No. 10604



Grinding wheel support

with cone Item No. 10616





DRILL GRINDING MACHINE BSG 60 full range equipment ITEM NO. 14369

The professional maschine

in the all-around carefree package

- ✓ for twist drills to 40 mm
- ✓ countersinks up to MK3
- ✓ and end mills

Full range equipment

- Clamping prism from 3 to 40 mm
- Corundum grinding wheel grit 60
- Cutter and countersink sharpening device SZVR
 Grinding wheel dresser with rotating diamond
 Collet set for SZVR

- DVD-manual
- Crank handle
 Adaptor for dust exhaust 32 mm
 Precision optical lens lighted

	Cam for cross hole countersinks	Item No. 10605
	Cam for two lip countersinks	Item No. 10606
	Spacer for 8 mm grinding wheels for 20 mm grinding wheels	Item No. 10694 Item No. 10690
The total section of the section of	Magnetic depth stop for cutters	Item No. 10621
	Cutting rost for cutters	Item No. 10622
	Stop dog for long drills	Item No. 10623
	Morse tapper sleeves for short MK-drills, MK 1 for short MK-drills, MK 2 for short MK-drills, MK 3	Item No. 14483 Item No. 14484 Item No. 14485

